

(12) **United States Patent**
Padovani et al.

(10) **Patent No.:** **US 8,351,372 B2**
(45) **Date of Patent:** **Jan. 8, 2013**

(54) **METHOD AND APPARATUS FOR HIGH RATE PACKET DATA TRANSMISSION**

(56) **References Cited**

(75) Inventors: **Roberto Padovani**, San Diego, CA (US); **Paul E. Bender**, San Diego, CA (US); **Peter J. Black**, La Jolla, CA (US); **Matthew S. Grob**, La Jolla, CA (US); **Jurg K. Hinderling**, San Diego, CA (US); **Nagabhushana T. Sindhushayana**, San Diego, CA (US); **Charles E. Wheatley, III**, Del Mar, CA (US)

U.S. PATENT DOCUMENTS
3,018,663 A 1/1962 Dunlop
3,534,264 A 10/1970 Blasbalg et al.
4,047,151 A 9/1977 Rydbeck et al.
4,256,925 A 3/1981 Goode
(Continued)

FOREIGN PATENT DOCUMENTS
CA 2239524 8/1998
(Continued)

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 711 days.

Harper, R.C., "Adaptive Phase and Amplitude Modulation on a Frequency Dispersive Fading Channel", IEEE Transactions on Communications, vol. Com-22, No. 6, Jun. 1974.

(Continued)

(21) Appl. No.: **11/540,286**

Primary Examiner — Bob Phunkulh

(22) Filed: **Sep. 29, 2006**

(74) Attorney, Agent, or Firm — Peng Zhu

(65) **Prior Publication Data**

US 2007/0025267 A1 Feb. 1, 2007

Related U.S. Application Data

(63) Continuation of application No. 10/809,213, filed on Mar. 25, 2004, now Pat. No. 7,184,426, which is a continuation of application No. 10/318,489, filed on Dec. 12, 2002, now Pat. No. 7,079,550, which is a continuation of application No. 08/963,386, filed on Nov. 3, 1997, now Pat. No. 6,574,211.

(57) **ABSTRACT**

In a data communication system capable of variable rate transmission, high rate packet data transmission improves utilization of the forward link and decreases the transmission delay. Data transmission on the forward link is time multiplexed and the base station transmits at the highest data rate supported by the forward link at each time slot to one mobile station. The data rate is determined by the largest C/I measurement of the forward link signals as measured at the mobile station. Upon determination of a data packet received in error, the mobile station transmits a NACK message back to the base station. The NACK message results in retransmission of the data packet received in error. The data packets can be transmitted out of sequence by the use of sequence number to identify each data unit within the data packets.

(51) **Int. Cl.**
H04W 4/00 (2009.01)

(52) **U.S. Cl.** **370/328; 370/468**

(58) **Field of Classification Search** None
See application file for complete search history.

46 Claims, 15 Drawing Sheets

